

# metalfire

| architectural fireplaces |

**model URBAN MF 1050-600-50 G 3S EXT  
+ glass + logburner + finishing frame  
+ cast iron (FULL VERSION)**

### Dimensions (mm)

- combustion chamber WxDxH 960 x 420 x 500
- combustion chamber with surrounding finishing frame included WxDxH 1050 x 600 x 500
- length of burner 500
- external WxDxH 1253 x 600 x 1675
- fresh air 2 x Ø150

### Technical Data (city gas)

for other types of gas see 'gasburner specifications' (options)

- appliance type B11AS/B14AS
- load 19,53 kW
- type of gas/pressure G20/20,25/25mBar
- gascat. I2E+, I2H, I2E, I2L

### Protection

- 'oxy-pilot'-protection
- ionization-protected pilot-flame
- secured flue pipe discharge
- secured oxygen supply

### Specifications


- control unit on the side
- finishing: heat-resistant black paint
- back: ribbed cast-iron
- lockable valve for fresh air and smoke gases
- log burner
- remote control with electronic ignition

### Options

- chimney fan RSVG 250 or 315:  
type depending on situation  
for further info contact the Metalfire dealer
- convection jacket (see options)

scale 1:20

[www.metalfire.eu](http://www.metalfire.eu)

EN 509 

General dimensional tolerances up to 6mm  
Metalfire preserves the right to modify specifications without previous notice

